

**ZPD204A**



**4 Channel H.264**  
Full - D1 Networking DVR



Model		ZPD204A
Special function	P2P function (IE)	Using Device ID and password to login <a href="http://www.vssweb.net">www.vssweb.net</a> , realize remote monitoring, playback and control like IE Web login. <b>No need any network, IP setting, easy for end user to use network function.</b>
	Web 2.0 function	Support multi browser, like: chrome,firefox,safari etc. realize remote display, playback.
System	Operation System	Embedded LINUX
	Pentaplex function	Live monitoring, recording, playback, backup & remote access
	Control Mode	USB mouse, Network
Video	Input	4 ch. BNC
	Standard	PAL (625line, 50f/s) NTSC (525line, 60f/s)
	Output	1 CVBS, BNC (1.0Vp-p,75 ohms)
		1 HDMI, 1.3a,support 1920x1080 Resolution 1 VGA,1920x1080,1280x1024,1280x720,1024x768 Resolution
Audio	Input	1 ch. RCA(Line in,2Vpp,1Kohms)
	Output	1 RCA (Line out,2Vpp,300ohms)
Display	Tour Display	Support
	Privacy Masking	Four zones for privacy masking for each channel
Recording	Video Compression	H.264
	Audio Compression	G.711A
	Image Encoding	Adjustable encoding quality, variable code stream/fixed code stream
	Dual Stream	Support
	Recording Resolution	4ch.D1
	Recording Mode	Manual, Schedule, motion detection, stop
	Time bar	Support
Video Detection&Alarm	Trigger Events	Recording, Tour,Email
	Motion Detection	396 (22x18) detection zone, variable sensitivity levels
	Capture	JPEG capture
Playback&Backup	Playback Channel	1/2/4 ch.
	Backup Mode	USB,HDD,Network Backup
Network	Ethernet	1 RJ-45 port (10M/100M)
	Network protocol	TCP/IP, UDP, HTTP, RTP/RTSP
	Network Functions	DHCP, PPPOE, DDNS,SMTP,SNTP,FTP,UPnP
	Remote Operation	Monitoring,PTZ control,playback,system setting,file download,log information
	Smart Phone	iPhone,iPad,Android,Blackberry,Windows Mobile
Hard Disk	Hard Disk	1 SATA ports
	HDD Management	Hard disk hibernation technology, HDD faulty alarm&raid
Auxiliary Interface	USB Interface	2 USB 2.0 ports
Environment	Power Supply	DC12V/2A
	Power Consumption	10W (without HDD)
	Working Environment	0℃—+45℃ / 10%—90%RH
	Dimension(W*D*H)	1U, 215x215x46mm(WxDxH)
	Weight	0.8Kg (without HDD)
	Installation	Desk type